Machine translation – not reviewed.
Unchanged original at the end.

Product data sheet (en)

Fireplace inserts Type: 333

YORK K I. TV 6.9 kW

Technical parameters

333 YOB

Performance

Nominal heat output (kW) / Adjustable heat output (kW)	10,0 / 5,0 - 12,0
Nominal heat output to the room (kW) / Adjustable heat output to the room (kW)	3,1 / 1,5 - 4,0
Nominal heat output to water (kW) / Adjustable heat output to water (kW)	6,9 / 3,5 - 8,0

Dimensions

Height (1) x Width (2) x Depth (3) (mm)	673 x 529 x 490
Internal dimensions of the firebox (w x h x d) / Maximum length of logs (mm)	380 x 355 x 270 / 340

Weight according to trim

without lining (kg)	85

Air

Central air inlet (7) / diameter (mm) / throat included in the stove	yes / Ø 100 / no
Secondary air control / Primary air control / Tertiary air supply	yes / no / yes
Automatic air supply control	No
Height of the central air intake axis from the floor (8) (mm)	106
Distance from the axis of the central air intake to the rearmost part of the product (8.1) (mm)	131
Air heat loss Vh (m3/ hour)	≤ 1,5

Parameters

Product classification	Type BE
Fuel: wood / wood briquettes [D / DB]	
Permissible fuel consumption at rated output (kg/ hour) [D / DB]	2,9 / 2,9
Heated space (m3)	100 - 240
Energy efficiency (%) [D / DB]	80,6 / 80,6
Seasonal energy efficiency ηs (%)	70,6
Energy Efficiency Index EEI / Energy Efficiency Class	107 / A
Minimum chimney draft (Pa)	12
Flue gas outlet temperature (°C) [D / DB]	300 / 300
Flue gas mass flow (g/ s) [D / DB]	8,5 / 8,5
CO concentration at 13% O2 (mg/ Nm3) [D / DB]	1078 / 1078
NOx concentration at 13% O2 (mg/ Nm3) [D / DB]	93 / 93
OGC concentration at 13% O2 (mg/ Nm3) [D / DB]	67 / 67
Dust concentration at 13% O2 (mg/ Nm3) [D / DB]	35 / 35
Multiple door closing	No
Intermittent operation (INT) / Continuous operation (NOC)	INT

Flue

Flue connection (4)	top / rear
Flue pipe diameter (mm)	Ø 150
Height of the rear flue axis from the floor (5) (mm)	522
Distance from the axis of the upper flue to the rearmost part of the product (6) (mm)	198
Chimney temperature class	T 400 G

Maximum chimney load mchim (kg)	-
Connection to a common chimney	No

Hot water exchanger


Cooling loop	No
Heat exchanger surface area (m2)	0,25
Maximum working pressure (bar)	2,5
Exchanger volume (l)	6
Heating water inlet height from floor (12.1) (mm)	404
Heating water outlet height from the floor (13.1) (mm)	614
Inlet temperature Tacc (°C)	55


Exams


EN 16510-1	Yes
EN 16510-2-2	Yes
I. BImSchV Level 2	Yes
ECODESIGN	Yes


Minimum clearance distances from flammable materials

Ceiling dC (mm)	>750
Part in front of the glass dP (mm)	800
Floor in front dF (mm)	0
Floor bottom dB (mm)	0
Lateral radiation area dL (mm)	350
Side part dS1 / dS2 / dS3 (mm)	200 / 200 / 200
Side part dS (mm)	200
Rear part dR (mm)	200
Minimum distance from walls made of non-combustible materials dnon (mm)	50










Machine translation – not reviewed.
Unchanged original at the end.

Dimensional sketch



Additional information


1	height	673 mm
2	width	529 mm
3	depth	490 mm
4	flue	Ø 150 mm
5	height of the rear flue axis from the floor	522 mm
6	distance from the axis of the upper flue to the rearmost part of the product	198 mm
7	central air supply	Ø 100 mm
8	height of the central air intake axis from the floor	106 mm
12	heating water inlet	3/4" ext.
12.1	heating water inlet height from the floor	404 mm
13	heating water outlet	3/4" ext.
13.1	height of heating water outlet from the floor	614 mm
22	burning intensity control - right open	

(A) When connecting the rear flue, it is necessary to set the flame spread to an oblique position.

(B) When connecting the upper flue, it is necessary to set the flame spread to a horizontal position.

Machine translation – not reviewed.
Unchanged original at the end.

Product control



Heating with wood and wood briquettes

Regulate the power only by controlling the burning intensity.

Manufacturer: ABX, spol. s r.o., Žitná 1091/3, 408 01 Rumburk, Czech Republic

phone: 412 332 523, 412 333 614, fax: 412 333 521, e-mail: info@abx.cz, website: www.abx.cz

Service: ABX s r.o., Plynární 1518/12, 408 01 Rumburk, tel.: 412 372 147, fax: 412 375 113, e-mail: reklamacie@abx.cz

As of: 13.4.2026

Machine translation – not reviewed.
Unchanged original at the end.

Technický list výrobku (cs)

Krbové vložky Typ: 333

YORK K I. TV 6,9 kW



Technický list výrobku (cs)

Krbové vložky Typ: 333

YORK K I. TV 6,9 kW

Technické parametry

333 YOB

Výkon

Jmenovitý tepelný výkon (kW) / **Regulovatelný tepelný výkon** (kW)	10,0 / 5,0 - 12,0
Jmenovitý tepelný výkon do prostoru (kW) / **Regulovatelný tepelný výkon do prostoru** (kW)	3,1 / 1,5 - 4,0
Jmenovitý tepelný výkon do vody (kW) / **Regulovatelný tepelný výkon do vody** (kW)	6,9 / 3,5 - 8,0

Rozměry

Výška (1) x **Šířka** (2) x **Hloubka** (3) (mm)	673 x 529 x 490
Vnitřní rozměr topeniště (š x v x h) / **Maximální délka polen** (mm)	380 x 355 x 270 / 340

Hmotnost podle obložení

bez obložení (kg)	85

Vzduch

Centrální přívod vzduchu (7) / **průměr** (mm) / **hrdlo součástí kamen**	ano / Ø 100 / ne
Ovládání sekundárního vzduchu / **Ovládání primárního vzduchu** / **Terciární přívod vzduchu**	ano / ne / ano
Automatická regulace přívodu vzduchu	ne
Výška osy centrálního přívodu vzduchu od podlahy (8) (mm)	106
Vzdálenost osy centrálního přívodu vzduchu k nejzadnější části výrobku (8.1) (mm)	131
Tepelná ztráta vzduchu V_h (m^3/hod)	≤ 1,5

Parametry

Klasifikace výrobku	Typ BE
Palivo: dřevo / dřevěné brikety [*D / DB*]	
Spotřeba přípustného paliva při jmenovitém výkonu (kg/hod) [*D / DB*]	2,9 / 2,9
Vytápěný prostor (m^3)	100 - 240
Energetická účinnost (%) [*D / DB*]	80,6 / 80,6
Sezónní energetická účinnost η_s (%)	70,6
Index energetické účinnosti EEI / **Třída energetické účinnosti**	107 / A
Minimální tah komína (Pa)	12
Výstupní teplota spalin (°C) [*D / DB*]	300 / 300
Hmotnostní tok spalin (g/s) [*D / DB*]	8,5 / 8,5
Koncentrace CO při 13 % O_2 (mg/Nm^3) [*D / DB*]	1078 / 1078
Koncentrace NO_x při 13 % O_2 (mg/Nm^3) [*D / DB*]	93 / 93
Koncentrace OGC při 13 % O_2 (mg/Nm^3) [*D / DB*]	67 / 67
Koncentrace prachu při 13 % O_2 (mg/Nm^3) [*D / DB*]	35 / 35
Vícenásobné zavírání dvířek	ne
Přerušovaný provoz (INT) / Nepřetržitý provoz (NOC)	INT

Kouřovod

Připojení kouřovodu (4)	horní / zadní
Průměr kouřovodu (mm)	Ø 150
Výška osy zadního kouřovodu od podlahy (5) (mm)	522
Vzdálenost osy horního kouřovodu k nejzadnější části výrobku (6) (mm)	198
Teplotní třída komínu	T 400 G

Maximální zatížení komínu m_{chim} (kg)	-
Připojení na společný komín	ne

Teplovodní výměník


Ochlazovací smyčka	ne
Teplosměnná plocha výměníku (m^2)	0,25
Maximální pracovní tlak (bar)	2,5
Objem výměníku (l)	6
Výška vstupu topné vody od podlahy (12.1) (mm)	404
Výška výstupu topné vody od podlahy (13.1) (mm)	614
Teplota na vstupu T_{acc} (°C)	55


Zkoušky


ČSN EN 16510-1	ano
ČSN EN 16510-2-2	ano
I. BImSchV Stufe 2	ano
EKODESIGN	ano


Minimální odstupové vzdálenosti od hořlavých materiálů

Strop d_C (mm)	>750
Část před sklem d_P (mm)	800
Podlaha v přední části d_F (mm)	0
Podlaha spodní část d_B (mm)	0
Boční oblast sálání d_L (mm)	350
Boční část d_{S1} / d_{S2} / d_{S3} (mm)	200 / 200 / 200
Boční část d_S (mm)	200
Zadní část d_R (mm)	200
Minimální vzdálenost od stěn z nehořlavých materiálů d_{non} (mm)	50










Rozměrový náčrt




Doplňující informace

1	výška	673 mm
2	šířka	529 mm
3	hloubka	490 mm
4	kouřovod	Ø 150 mm
5	výška osy zadního kouřovodu od podlahy	522 mm
6	vzdálenost osy horního kouřovodu k nejzadnější části výrobku	198 mm
7	centrální přívod vzduchu	Ø 100 mm
8	výška osy centrálního přívodu vzduchu od podlahy	106 mm
12	vstup topné vody	3/4" vnější
12.1	výška vstupu topné vody od podlahy	404 mm
13	výstup topné vody	3/4" vnější
13.1	výška výstupu topné vody od podlahy	614 mm
22	ovládání intenzity hoření - vpravo otevřeno	

(A) Při napojení zadního kouřovodu, je nutné nastavit rozrážku plamene do šikmé polohy.

(B) Při napojení horního kouřovodu, je nutné nastavit rozrážku plamene do vodorovné polohy.

Ovládání produktu



Topení dřevem a dřevěnými briketami

Výkon regulujte jen pomocí ovládání intenzity hoření.

Výrobce: ABX, spol. s r.o., Žitná 1091/3, 408 01 Rumburk, Česká republika

tel.: 412 332 523, 412 333 614, fax: 412 333 521, e-mail: info@abx.cz, web: www.abx.cz

Servis: ABX s r.o., Plynární 1518/12, 408 01 Rumburk, tel.: 412 372 147, fax: 412 375 113, e-mail: reklamace@abx.cz

Stav ke dni: 13.4. 2026