Machine translation – not reviewed.
Unchanged original at the end.

Product data sheet (en)

Fireplace stove Type: 390

BALTIC 4650-6-II

Technical parameters

Performance

	390 BAB
Nominal heat output (kW) / Adjustable heat output (kW)	6,5 / 3,0 - 8,5

Dimensions

Height (1) x Width (2) x Depth (3) (mm)	1013 x 544 x 424
Internal dimensions of the firebox (w x h x d) / Maximum length of logs (mm)	355 x 450 x 300 / 300

Weight according to trim

stone (kg)	130
sheet metal (kg)	93

Air

Central air inlet (7) / diameter (mm) / throat included in the stove	yes / Ø 100 / no
Secondary air control / Primary air control / Tertiary air supply	yes / yes / yes
Automatic air supply control	No
Height of the central air intake axis from the floor (8) (mm)	283
Air heat loss Vh (m3/ hour)	≤ 1,5

Parameters

Product classification	Type BE
Fuel: wood / wood briquettes / brown coal briquettes [D / DB / HB]	
Permissible fuel consumption at rated output (kg/ hour) [D / DB / HB]	2,0 / 2,0 / 1,6
Heated space (m3)	70 - 170
Energy efficiency (%) [D / DB / HB]	80,4 / 80,7 / 83,4
Seasonal energy efficiency ηs (%)	70,4
Energy Efficiency Index EEI / Energy Efficiency Class	107 / A
Minimum chimney draft (Pa)	12
Flue gas outlet temperature (°C) [D / DB / HB]	281 / 272 / 288
Flue gas mass flow (g/ s) [D / DB / HB]	6,7 / 6,9 / 5,6
CO concentration at 13% O2 (mg/ Nm3) [D / DB / HB]	1103 / 956 / 722
NOx concentration at 13% O2 (mg/ Nm3) [D / DB / HB]	118 / 71 / 112
OGC concentration at 13% O2 (mg/ Nm3) [D / DB / HB]	61 / 69 / 52
Dust concentration at 13% O2 (mg/ Nm3) [D / DB / HB]	39 / 38 / 36
Multiple door closing	Yes
Intermittent operation (INT) / Continuous operation (NOC)	INT

Flue


Flue connection (4)	top / rear
Flue pipe diameter (mm)	Ø 150
Height of the rear flue axis from the floor (5) (mm)	860
Distance from the axis of the upper flue to the rearmost part of the product (6) (mm)	130
Chimney temperature class	T 400 G
Maximum chimney load mchim (kg)	-
Connection to a common chimney	No


Exams


EN 16510-1	Yes
EN 16510-2-1	Yes
I. BImSchV Level 2	Yes
ECODESIGN	Yes


Minimum clearance distances from flammable materials

Ceiling dC (mm)	>750
Part in front of the glass dP (mm)	800
Floor in front dF (mm)	0
Floor bottom dB (mm)	0
Lateral radiation area dL (mm)	400
Side part dS1 / dS2 / dS3 (mm)	200 / 200 / 200
Side part dS (mm)	200
Rear part dR (mm)	200
Minimum distance from walls made of non-combustible materials dnon (mm)	50










Machine translation – not reviewed.
Unchanged original at the end.

Dimensional sketch




Additional information

1	height	1013 mm
2	width	544 mm
3	depth	424 mm
4	flue	Ø 150 mm
5	height of the rear flue axis from the floor	860 mm
6	distance from the axis of the upper flue to the rearmost part of the product	130 mm
7	central air supply	Ø 100 mm
8	height of the central air intake axis from the floor	283 mm
9	primary air supply control - retracted open	
10	secondary air supply control - retracted open	

Machine translation – not reviewed.
Unchanged original at the end.

Product control



Heating with wood and wood briquettes

Regulate the output only using the secondary air regulator (position 10). The manufacturer recommends closing the primary air intake (position 9) completely or almost completely after the stove has ignited.

Heating with brown coal briquettes Note: Heating with brown coal briquettes requires an increase in the primary air supply. The degree of increase must be verified according to the specific draft ratios of the stove and chimney.

Regulate the output only using the primary air regulator (position 9). The manufacturer recommends closing the secondary air intake (position 10) completely or almost completely after the stove has ignited.

Manufacturer: ABX, spol. s r.o., Žitná 1091/3, 408 01 Rumburk, Czech Republic

phone: 412 332 523, 412 333 614, fax: 412 333 521, e-mail: info@abx.cz, website: www.abx.cz

Service: ABX s r.o., Plynární 1518/12, 408 01 Rumburk, tel.: 412 372 147, fax: 412 375 113, e-mail: reklamacie@abx.cz

As of: 14.4.2026

Machine translation – not reviewed.
Unchanged original at the end.

Technický list výrobku (cs)

Krbová kamna Typ: 390

BALTIK 4650-6-II



Technický list výrobku (cs)

Krbová kamna Typ: 390

BALTIK 4650-6-II

Technické parametry

390 BAB

Výkon

Jmenovitý tepelný výkon (kW) / **Regulovatelný tepelný výkon** (kW)	6,5 / 3,0 - 8,5

Rozměry

Výška (1) x **Šířka** (2) x **Hloubka** (3) (mm)	1013 x 544 x 424
Vnitřní rozměr topeniště (š x v x h) / **Maximální délka polen** (mm)	355 x 450 x 300 / 300

Hmotnost podle obložení

kámen (kg)	130
plech (kg)	93

Vzduch

Centrální přívod vzduchu (7) / **průměr** (mm) / **hrdlo součástí kamen**	ano / Ø 100 / ne
Ovládání sekundárního vzduchu / **Ovládání primárního vzduchu** / **Terciární přívod vzduchu**	ano / ano / ano
Automatická regulace přívodu vzduchu	ne
Výška osy centrálního přívodu vzduchu od podlahy (8) (mm)	283
Tepelná ztráta vzduchu V_h (m^3/hod)	≤ 1,5

Parametry

Klasifikace výrobku	Typ BE
Palivo: dřevo / dřevěné brikety / hnědouhelné brikety [*D / DB / HB*]	
Spotřeba přípustného paliva při jmenovitém výkonu (kg/hod) [*D / DB / HB*]	2,0 / 2,0 / 1,6
Vytápěný prostor (m^3)	70 - 170
Energetická účinnost (%) [*D / DB / HB*]	80,4 / 80,7 / 83,4
Sezónní energetická účinnost η_s (%)	70,4
Index energetické účinnosti EEI / **Třída energetické účinnosti**	107 / A
Minimální tah komína (Pa)	12
Výstupní teplota spalin (°C) [*D / DB / HB*]	281 / 272 / 288
Hmotnostní tok spalin (g/s) [*D / DB / HB*]	6,7 / 6,9 / 5,6
Koncentrace CO při 13 % O_2 (mg/Nm^3) [*D / DB / HB*]	1103 / 956 / 722
Koncentrace NO_x při 13 % O_2 (mg/Nm^3) [*D / DB / HB*]	118 / 71 / 112
Koncentrace OGC při 13 % O_2 (mg/Nm^3) [*D / DB / HB*]	61 / 69 / 52
Koncentrace prachu při 13 % O_2 (mg/Nm^3) [*D / DB / HB*]	39 / 38 / 36
Vícenásobné zavírání dvířek	ano
Přerušovaný provoz (INT) / **Nepřetržitý provoz (NOC)**	INT

Kouřovod


Připojení kouřovodu (4)	horní / zadní
Průměr kouřovodu (mm)	Ø 150
Výška osy zadního kouřovodu od podlahy (5) (mm)	860
Vzdálenost osy horního kouřovodu k nejzadnější části výrobku (6) (mm)	130
Teplotní třída komínu	T 400 G
Maximální zatížení komínu m_{chim} (kg)	-
Připojení na společný komín	ne


Zkoušky


ČSN EN 16510-1	ano
ČSN EN 16510-2-1	ano
I. BImSchV Stufe 2	ano
EKODESIGN	ano


Minimální odstupové vzdálenosti od hořlavých materiálů

Strop d_C (mm)	>750
Část před sklem d_P (mm)	800
Podlaha v přední části d_F (mm)	0
Podlaha spodní část d_B (mm)	0
Boční oblast sálání d_L (mm)	400
Boční část d_{S1} / d_{S2} / d_{S3} (mm)	200 / 200 / 200
Boční část d_S (mm)	200
Zadní část d_R (mm)	200
Minimální vzdálenost od stěn z nehořlavých materiálů d_{non} (mm)	50











Rozměrový náčrt



Doplňující informace

1	výška	1013 mm
2	šířka	544 mm
3	hloubka	424 mm
4	kouřovod	Ø 150 mm
5	výška osy zadního kouřovodu od podlahy	860 mm
6	vzdálenost osy horního kouřovodu k nejzadnější části výrobku	130 mm
7	centrální přívod vzduchu	Ø 100 mm
8	výška osy centrálního přívodu vzduchu od podlahy	283 mm
9	ovládání primárního přívodu vzduchu - zasunuto otevřeno	
10	ovládání sekundárního přívodu vzduchu - zasunuto otevřeno	

Ovládání produktu



Topení dřevem a dřevěnými briketami

Výkon regulujte jen pomocí sekundárního regulátoru vzduchu (pozice 10). Primární přisávání vzduchu (pozice 9) výrobce doporučuje po rozhoření kamen uzavřít zcela či téměř.

Topení hnědouhelnými briketami

Pozn.: Topení hnědouhelnými briketami vyžaduje zvětšení přívodu primárního vzduchu. Míru zvětšení je třeba ověřit dle konkrétních tahových poměrů kamen a komína.

Výkon regulujte jen pomocí primárního regulátoru vzduchu (pozice 9). Sekundární přisávání vzduchu (pozice 10) výrobce doporučuje po rozhoření kamen uzavřít zcela či téměř.

Výrobce: ABX, spol. s r.o., Žitná 1091/3, 408 01 Rumburk, Česká republika

tel.: 412 332 523, 412 333 614, fax: 412 333 521, e-mail: info@abx.cz, web: www.abx.cz

Servis: ABX s r.o., Plynární 1518/12, 408 01 Rumburk, tel.: 412 372 147, fax: 412 375 113, e-mail: reklamace@abx.cz

Stav ke dni: 14.4. 2026