Product data sheet (en)

Tiled stove Type: 385

BAVARIA EXCLUSIVE

Technical parameters

Performance

	385 BXA
Nominal heat output (kW) / Adjustable heat output (kW)	7,0 / 3,5 - 9,0

Dimensions

Height (1) x Width (2) x Depth (3) (mm)	993 x 760 x 496
Internal dimensions of the firebox (w x h x d) / Maximum length of logs (mm)	375 x 485 x 295 / 330

Weight according to trim

stove (kg)	140

Air

Central air inlet (7) / diameter (mm) / throat included in the stove	yes / Ø 100 / no
Secondary air control / Primary air control / Tertiary air supply	yes / yes / yes
Automatic air supply control	No
Height of the central air intake axis from the floor (8) (mm)	253
Distance from the axis of the central air intake to the rearmost part of the product (8.1) (mm)	145
Air heat loss Vh (m3/hour)	≤ 1,5

Parameters

Product classification	Type BE
Fuel: wood / wood briquettes [D / DB]	
Permissible fuel consumption at rated output (kg/hour) [D / DB]	2,1 / 2,1
Heated space (m3)	70 - 180
Energy efficiency (%) [D / DB]	80,4 / 80,2
Seasonal energy efficiency ηs (%)	70,4
Energy Efficiency Index EEI / Energy Efficiency Class	107 / A+
Minimum chimney draft (Pa)	12
Flue gas outlet temperature (°C) [D / DB]	334 / 268
Flue gas mass flow (g/s) [D / DB]	6,0 / 7,4
CO concentration at 13% O2 (mg/Nm3) [D / DB]	833 / 1240
NOx concentration at 13% O2 (mg/Nm3) [D / DB]	76 / 59
OGC concentration at 13% O2 (mg/Nm3) [D / DB]	72 / 71
Dust concentration at 13% O2 (mg/Nm3) [D / DB]	31 / 40
Multiple door closing	No
Intermittent operation (INT) / Continuous operation (NOC)	INT

Machine translation. Technical review pending.
Complete unchanged original at the end. Translation is not manufacturer-approved.

Flue


Flue connection (4)	top / rear
Flue pipe diameter (mm)	Ø 150
Height of the rear flue axis from the floor (5) (mm)	808
Distance from the axis of the upper flue to the rearmost part of the product (6) (mm)	192
Chimney temperature class	T 400 G
Maximum chimney load mchim (kg)	-
Connection to a common chimney	Yes


Exams


EN 16510-1	Yes
EN 16510-2-1	Yes
I. BImSchV Level 2	Yes
ECODESIGN	Yes


Minimum clearance distances from flammable materials

Ceiling dC (mm)	>800
Part in front of the glass dP (mm)	800
Floor in front dF (mm)	0
Floor bottom dB (mm)	0
Lateral radiation area dL (mm)	450
Side part dS1 / dS2 / dS3 (mm)	200 / 200 / 200
Side part dS (mm)	200
Rear part dR (mm)	200
Minimum distance from walls made of non-combustible materials dnon (mm)	50










Machine translation. Technical review pending.
Complete unchanged original at the end. Translation is not manufacturer-approved.

Dimensional sketch




Additional information


1	height	993 mm
2	width	760 mm
3	depth	496 mm
4	flue	Ø 150 mm
5	height of the rear flue axis from the floor	808 mm
6	distance from the axis of the upper flue to the rearmost part of the product	192 mm
7	central air supply	Ø 100 mm
8	height of the central air intake axis from the floor	253 mm
8.1	distance from the axis of the central air intake to the rearmost part of the product	145 mm
22	burning intensity control - right open	

Machine translation. Technical review pending.
Complete unchanged original at the end. Translation is not manufacturer-approved.

Assembly diagram



Product control



Heating with wood and wood briquettes

Regulate the power only by controlling the burning intensity.

Manufacturer: ABX, spol. s r.o., Žitná 1091/3, 408 01 Rumburk, Czech Republic

phone: 412 332 523, 412 333 614, fax: 412 333 521, e-mail: info@abx.cz, website: www.abx.cz

Service: ABX s r.o., Plynární 1518/12, 408 01 Rumburk, tel.: 412 372 147, fax: 412 375 113, e-mail: reklamacie@abx.cz

As of: 06.8.2026

Machine translation. Technical review pending.
Complete unchanged original at the end. Translation is not manufacturer-approved.

Technický list výrobku (cs)

Kachlová kamna Typ: 385

BAVARIA EXKLUSIVE



Technický list výrobku (cs)

Kachlová kamna Typ: 385

BAVARIA EXKLUSIVE

Technické parametry

385 BXA

Výkon

Jmenovitý tepelný výkon (kW) / **Regulovatelný tepelný výkon** (kW)	7,0 / 3,5 - 9,0

Rozměry

Výška (1) x **Šířka** (2) x **Hloubka** (3) (mm)	993 x 760 x 496
Vnitřní rozměr topeniště (š x v x h) / **Maximální délka polen** (mm)	375 x 485 x 295 / 330

Hmotnost podle obložení

kachle (kg)	140

Vzduch

Centrální přívod vzduchu (7) / **průměr** (mm) / **hrdlo součástí kamen**	ano / Ø 100 / ne
Ovládání sekundárního vzduchu / **Ovládání primárního vzduchu** / **Terciární přívod vzduchu**	ano / ano / ano
Automatická regulace přívodu vzduchu	ne
Výška osy centrálního přívodu vzduchu od podlahy (8) (mm)	253
Vzdálenost osy centrálního přívodu vzduchu k nejzadnější části výrobku (8.1) (mm)	145
Tepelná ztráta vzduchu V_h (m^3/hod)	≤ 1,5

Parametry

Klasifikace výrobku	Typ BE
Palivo: dřevo / dřevěné brikety [*D / DB*]	
Spotřeba přípustného paliva při jmenovitém výkonu (kg/hod) [*D / DB*]	2,1 / 2,1
Vytápěný prostor (m^3)	70 - 180
Energetická účinnost (%) [*D / DB*]	80,4 / 80,2
Sezónní energetická účinnost η_s (%)	70,4
Index energetické účinnosti EEI / **Třída energetické účinnosti**	107 / A+
Minimální tah komína (Pa)	12
Výstupní teplota spalin (°C) [*D / DB*]	334 / 268
Hmotnostní tok spalin (g/s) [*D / DB*]	6,0 / 7,4
Koncentrace CO při 13 % O_2 (mg/Nm^3) [*D / DB*]	833 / 1240
Koncentrace NO_x při 13 % O_2 (mg/Nm^3) [*D / DB*]	76 / 59
Koncentrace OGC při 13 % O_2 (mg/Nm^3) [*D / DB*]	72 / 71
Koncentrace prachu při 13 % O_2 (mg/Nm^3) [*D / DB*]	31 / 40
Vícenásobné zavírání dvířek	ne
Přerušovaný provoz (INT) / Nepřetržitý provoz (NOC)	INT

Kouřovod


Připojení kouřovodu (4)	horní / zadní
Průměr kouřovodu (mm)	Ø 150
Výška osy zadního kouřovodu od podlahy (5) (mm)	808
Vzdálenost osy horního kouřovodu k nejzadnější části výrobku (6) (mm)	192
Teplotní třída komínu	T 400 G
Maximální zatížení komínu m_{chim} (kg)	-
Připojení na společný komín	ano


Zkoušky


ČSN EN 16510-1	ano
ČSN EN 16510-2-1	ano
I. BImSchV Stufe 2	ano
EKODESIGN	ano


Minimální odstupové vzdálenosti od hořlavých materiálů

Strop d_C (mm)	>800
Část před sklem d_P (mm)	800
Podlaha v přední části d_F (mm)	0
Podlaha spodní část d_B (mm)	0
Boční oblast sálání d_L (mm)	450
Boční část d_{S1} / d_{S2} / d_{S3} (mm)	200 / 200 / 200
Boční část d_S (mm)	200
Zadní část d_R (mm)	200
Minimální vzdálenost od stěn z nehořlavých materiálů d_{non} (mm)	50











Rozměrový náčrt




Doplňující informace

1	výška	993 mm
2	šířka	760 mm
3	hloubka	496 mm
4	kouřovod	Ø 150 mm
5	výška osy zadního kouřovodu od podlahy	808 mm
6	vzdálenost osy horního kouřovodu k nejzadnější části výrobku	192 mm
7	centrální přívod vzduchu	Ø 100 mm
8	výška osy centrálního přívodu vzduchu od podlahy	253 mm
8.1	vzdálenost osy centrálního přívodu vzduchu k nejzadnější části výrobku	145 mm
22	ovládání intenzity hoření - vpravo otevřeno	

Montážní schéma



Ovládání produktu



Topení dřevem a dřevěnými briketami
Výkon regulujte jen pomocí ovládání intenzity hoření.

Výrobce: ABX, spol. s r.o., Žitná 1091/3, 408 01 Rumburk, Česká republika
tel.: 412 332 523, 412 333 614, fax: 412 333 521, e-mail: info@abx.cz, web: www.abx.cz
Servis: ABX s r.o., Plynární 1518/12, 408 01 Rumburk, tel.: 412 372 147, fax: 412 375 113, e-mail: reklamace@abx.cz
Stav ke dni: 06.8. 2026